

OHAUS Indicatoren

	T31P	T31XW	T51P	T51XW	T71P	T71XW
Bereik (Max)	5-20,000 kg		0.5 - 30,000 t		0.5 - 50,000 t	
Display resolutie	20,000		30,000		50,000	
IJkwaardig resolutie	6000		10,000		10,000	
Schaaldeel	0.001 - 20		0.00001 - 1000		0.00001 - 1000	
Eenheden	kg, lbs, g		kg, lbs, g, t, oz, custom		kg, lbs, g, t, oz, custom	
Functies	Wegen, stukstelling		Wegen, stukstelling, checkwegen		Wegen, stukstelling, checkwegen, dynamisch wegen, hold	
Kleinste stuksgewicht	1:20,000		1:300,000		1:500,000	
Display	25mm, LCD, 6x7 segment, backlit		25mm, LCD, 6x7 segment, backlit		LCD, 6x7 seg 25mm, 2 ^e regel AN 3x LED L/P/H (Y/G/R)	
Toetsen	4x Mechanisch	4x Membraan	4x Mechanisch	4x Membraan	17x Membraan	
Behuizing	ABS	RVS	ABS	RVS	ABS	RVS
Afdichting	IP54	IP66	IP54	IP66	IP54	IP66
LC voeding	5 VDC		5 VDC		5 VDC	
Aantal opnemers	Max. 4x 350 Ohm		Max. 8x 350 Ohm		Max. 8x 350 Ohm	
Ingang gevoeligheid	<3mV/V		<3mV/V		<3mV/V	
Stabilisatie tijd	<2 sec.		<2 sec.		<2 sec.	
Nul tracking	uit, 0.5, 1, 2, 3d		uit, 0.5, 1, 2, 3d		uit, 0.5, 1, 2, 3d	
Nul range	0, 2, 100%		0, 2, 100%		0, 2, 100%	
Interface	1x RS232		1x RS232 + Input (remote button)		1x RS232 + Input (remote button) 1x RS232/RS485 (optie)	
Opties	Geen		DC Relais kit (3x output)		DC Relais kit (3x output) / Alibi	
Afmetingen (LxDxH)	210x71x168	212x71x149	260x71x168	262x76x149	260x71x168	262x76x149
Voeding	9-12VDC PS 100hr accu	100-240VAC 50-60Hz	100-240VAC / 50-60Hz 6x oplaadbare batterij		100-240VAC / 50-60Hz 6x oplaadbare batterij	
Gewicht	1.6kg	2.9kg	1.5kg	3.5kg	1.5kg	3.5kg