



## WEIGHT AND CABLE LENGTHS

---

### LOAD CELL WEIGHT(unpacked)

LC-type	Capacity	Weight (kg)
SHBxR	All	0,4
5102	50 / 200 lbs	0,7
	0,5 6 2,5 Klbs	0,8
	5 / 10 Klbs	1,8
5123/9123	0,5 6 2 t	0,9
	5 t	1,9
HCB	0,5 6 2 t	1,2
SSB	0,5 6 2 t	2,0
	5 t	4,2
RLC	0,5 / 1 t	0,9
	2 6 5 t	1,5
CHP	50 Klbs	7,5
	100 Klbs	8,2
	150 / 200 Klbs	20
CSP-M/CP-M	10 / 25 t	2,7 / 3,7
	40 / 60 t	7,0 / 8,0
	100 t	18
5103/9103	5 6 20 Klbs	2,3
	30 6 60 Klbs	7,3
	100 6 150 Klbs	11
	200 6 250 Klbs	21
5223/5222	All	7,3
BSP	50 / 125 kg	0,6
	250 / 500 kg	0,8
	1250 kg	1,2
	2,5 / 5 t	2,2
363/9363	50 / 100 kg	0,4
	250 / 500 kg	0,5
	1000 kg	0,6
	2500 / 5000 kg	1,5
USP	100 lbs	0,9
	250 6 1000 lbs	1,8
	2,5 6 10 Klbs	3,6
	25 Klbs	9,1
	50 Klbs	25
	100 Klbs	41
	200 / 300 Klbs	57
HPS	6 6 30 kg	0,9
	60 kg	1,2
652	All	2,3

SCC	10t 40t	3 8
MWP	10t	16
KSR	6t	1
642		0,8
263D	250 lbs	1,3
LC30		1,5
Surge protect.device		0,3

## LOAD CELL CABLE LENGTH

LC-type	Capacity	Cable length (m)	Tolerance (m)
SHBxR	All	3	" 0,2
9102	All	3	" 0,2
HCB	All	3	" 0,2
SSB	All	5	" 0,5
RLC	0.5, 1 t	3	" 0,2
	2, 3.5, 5 t	5	" 0,3
CSP-M	10 t	10	" 0,5
	256 100 t	20	" 1,0
BSP	All	10	" 0,5
HPS	All	7	" 0,4

Note: Other cable lengths optional.

Please inform us if the standard cable length is critical for a specific application.

### Revere Transducers Europe

Postbus 6909  
4802 HX Breda  
The Netherlands  
Tel. (+31)76-5480700  
Fax. (+31)76-5412854